

纵向电光Q开关

昊量光电KD*P, BBO, RTP and Lithium Niobate 等电光调制器, 和Q开关.

产品孔径最大可达50mm, 尺寸最小可达26.4mm*19mm。

产品参考损伤阈值:

850 Megawatts/cm for pulses <20 nsec wide

10 Gigawatts/cm for pulses <500 psec wide

20 Gigawatts/cm for pulses <100 psec wide



匹配电源参数:

DC-5Khz, 10KV最高输出电压, <3ns上升下降沿

材料	型号	半波电压	半波电压	孔径 (mm)	透过率	消光比
		@694 (KV)	@1064 (KV)			
KD*P (400nm - 1100nm)	1041	2.1	3.2	10	98%	1000:1
	1042	1.1	1.7	10	95%	800:1
	1043	2.2	3.3	16	98%	800:1
	1044	1.2	1.7	16	95%	700:1
	1144-25	4.3	6.5	25	98%	1500: 1
	1144-30	4.5	6.8	30	97%	1000: 1
	1144-50	4.9	7.5	50	95%	700:1
	1148	2.1	3.2	10	98%	2000:1
BBO (350nm -1300nm)	1150-3	3.4	5.8	3	98%	1000: 1
	1150-6	6.9	11.5	6	98%	1000: 1
RTP (400nm-1300nm)	1147-4	<u>800@633</u>	1600	3.5	98%	200: 1
	1147-8	<u>1800@633</u>	3600	7.5	98%	200: 1

Aunion Tech Co.,Ltd

Room 905, F Building, Everbright Convention and Exhibition Center, No. 86 Caobao Road, Shanghai 200235, China

Tel: +86-21-51083793

E-Mail: info@auniontech.com

Fax:+86-21-34241962

Website: www.auniontech.com